



## 02000 Motor Oil 15W-40 Turbo Universal

Document version: Apr 29, 2024



### Description

This universal mineral motor oil has been specially developed for normal duty petrol engines and diesel engines of cars. This motor oil is also suitable for turbo diesel engines.

### Application manual

According to the specifications of

ACEA A3/B4 / E2  
API CG-4 / SL  
Allison C4  
Caterpillar TO-2  
MAN M 271  
MB 228.1  
Volvo VDS

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
02001	1 L	6	450
02004	4 L	4	112
02005	5 L	4	112
02020	20 L	1	30
02060	60 L	1	6
02205	205 L	1	2
02999	1000 L	1	-
P02000	1 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.873	kg/l
Viscosity	15W-40	
Kinematic Viscosity at 40°C	90.5	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	13.5	mm <sup>2</sup> /s
Viscosity Index	151	
Flashpoint COC	200	°C
Pourpoint	-30	°C
Total Base Number	8.4	mgKOH/g
Sulphated Ash	1	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.