



## 04000S Motor Oil 10W-40 Semi Synthetic SN

Document version: Apr 29, 2024



### Description

This semi synthetic motor oil is designed for lubrication of four stroke petrol and diesel engines. The formulation is based on highly refined base oils and the high quality ensures excellent engine protection and durability with very good low temperature fluidity.

### According to the specifications of

ACEA A3/B4  
API CF / SN  
MB-Approval 229.3  
VW 501.01 / 505.00

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04001S	1 L	6	450
04004S	4 L	4	112
04005S	5 L	4	112
04020S	20 L	1	30
04060S	60 L	1	6
04205S	205 L	1	2
04999S	1000 L	1	-
P04000S	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.859	kg/l	ASTM D4052
Viscosity	10W-40		
Kinematic Viscosity at 40°C	93	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	13.9	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	153		ASTM D2270
Dynamic Viscosity at -25°C	6820	mPa.s	ASTM D5293
Flashpoint COC	220	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	8.4	mgKOH/g	ASTM D2896
Sulphated Ash	1.03	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.