



05000DX1 Motor Oil 5W-30 Premium Synthetic DX1

Document version: Apr 29, 2024



Description

This premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs. Developed for better low speed pre-ignition (LSPI) protection, particularly for Opel/GM small displacement turbo charged engines. This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions. Due the excellent thin-flowability this engine oil offers excellent cold start properties.

According to the specifications of

API SN Plus / SN-RC / SP / SP-RC
Chrysler MS-13340 / MS-6395
Fiat 9.55535-CR1
Ford WSS-M2C946-A / WSS-M2C961-A1
GM dexos™1 Gen 3 License No. D335ABDI046
ILSAC GF-5 / GF-6A

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|-----------|--------|----------------|------------------|
| 05001DX1 | 1 L | 6 | 450 |
| 05005DX1 | 5 L | 4 | 112 |
| 05020DX1 | 20 L | 1 | 30 |
| 05060DX1 | 60 L | 1 | 12 |
| 05205DX1 | 205 L | 1 | 2 |
| 05999DX1 | 1000 L | 1 | - |
| P05000DX1 | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|-------|--------------------|------------|
| Density at 15°C | 0.848 | kg/l | ASTM D4052 |
| Viscosity | 5W-30 | | |
| Kinematic Viscosity at 40°C | 60.7 | mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 10.8 | mm ² /s | ASTM D445 |
| Viscosity Index | 172 | | ASTM D2270 |
| Flashpoint COC | 225 | °C | ASTM D92 |
| Pourpoint | -36 | °C | ASTM D7346 |
| Total Base Number | 8.5 | mgKOH/g | ASTM D2896 |

These characteristics are typical of current production. Variations in these characteristics may occur.