



05000EDT Motor Oil 0W-30 Premium Synthetic EDT

Document version: Apr 29, 2024



Description

This premium synthetic Motor oil has been specially developed for use in Ford Duratorq TDCi Euro 6 engines and prescribed as mandatory for these engines fitted with exhaust gas after-treatment systems and turbochargers. Due to the balanced formulation and carefully selected additive package contained within, this oil is recommended and suitable for Duratorq Euro 6 engines with extended drain intervals, low CO2 emissions and high fuel-saving features. This high performance engine oil is also suitable for vehicles where the SAE 0W-30 with ACEA C2 specification is requested.

According to the specifications of

ACEA C2
Ford WSS-M2C950-A
Jaguar/Land Rover STJLR.03.5007

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001EDT	1 L	6	450
05005EDT	5 L	4	112
05020EDT	20 L	1	30
05B20EDT	20 L	1	-
05060EDT	60 L	1	6
05205EDT	205 L	1	2
05999EDT	1000 L	1	-
P05000EDT	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.841	kg/l	ASTM D4052
Viscosity SAE	0W-30		
Kinematic Viscosity at 40°C	48	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	9.8	mm ² /s	ASTM D445
Viscosity Index	196		ASTM D2270
Dynamic Viscosity at -35°C	5600	mPa.s	ASTM D5293
Flashpoint COC	210	°C	ASTM D92
Pourpoint	-48	°C	ASTM D7346
Total Base Number	7.8	mgKOH/g	ASTM D2896
Sulphated Ash	0.79	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.