



## 05000JP Motor Oil 0W-20 Premium Synthetic JP

Document version: Apr 29, 2024



### Description

This premium synthetic motor oil SAE 0W-20 has been specially developed for high-tech engines of Japanese, USA and European cars manufacturers and ensures an extremely economical fuel consumption. Due to the organic, friction-reducing additives contained within, this oil reduces motor wear to the minimum. This oil has a very low viscosity of SAE 0W-20. Note: The use of this oil in motors designed for motor oil with a high viscosity may result in insufficient oil circulation, leaks and other problems.

### According to the specifications of

API SN Plus / SN-RC / SP / SP-RC  
Chrysler MS-6395  
Fiat 9.55535-CR1  
Ford WSS-M2C947-A / WSS-M2C962-A1  
GM dexos™1 Gen 3 License No. D335BCDL046  
ILSAC GF-5 / GF-6A

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001JP	1 L	6	450
05005JP	5 L	4	112
05020JP	20 L	1	30
05B20JP	20 L	1	-
05060JP	60 L	1	6
05205JP	205 L	1	2
05999JP	1000 L	1	-
P05000JP	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	
Viscosity	0W-20		
Kinematic Viscosity at 40°C	45.6	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	8.53	mm <sup>2</sup> /s	
Viscosity Index	167		
Pourpoint	-39	°C	
Total Base Number	7.4	mgKOH/g	
Sulphated Ash	0.79	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.