



05000ST Motor Oil 5W-30 Premium Synthetic ST

Document version: Apr 29, 2024



Description

This Premium Synthetic 'Mid SAPS ' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. This special formulation complies with the Stellantis FPW9.55535/03 specification, which is mandatory for DV5R engines up to OPR 16885 and for the EB2 Gen1 (2013-2019) 1.2L PureTech engines. These D5VR and EB2 engines are used in Citroën, DS, Peugeot, Fiat, Toyota, Opel and Vauxhall. Optimized cleanliness reduces wear and increases the lifetime of the mechanical components and engine. This engine oil is also suitable for engines requiring the PSA B71 2290 specification with viscosity grade 5W-30.

Application manual

According to the specifications of

ACEA C3
API SN Plus
PSA B71 2290
Stellantis FPW9.55535/03

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 05001ST | 1 L | 6 | 450 |
| 05005ST | 5 L | 4 | 112 |
| 05020ST | 20 L | 1 | 30 |
| 05060ST | 60 L | 1 | 6 |
| 05205ST | 205 L | 1 | 2 |
| P05000ST | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|-------|--------------------|------------|
| Density at 15°C | 0.847 | kg/l | ASTM D4052 |
| Kinematic Viscosity at 40°C | 66.3 | mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 11.3 | mm ² /s | ASTM D445 |
| Viscosity Index | 170 | | ASTM 2270 |
| Flashpoint COC | 254 | °C | ASTM D92 |
| Pourpoint | -42 | °C | ASTM D97 |

These characteristics are typical of current production. Variations in these characteristics may occur.