



# 14000 Gear Oil 85W-140 GL-5 Mineral Hypoid Oil

Document version: Apr 29, 2024



## Description

This mineral SAE 85W-140 gear oil has been specially developed for lubrication of heavy duty hypoid drives in rear axles and in all transmissions where a mineral GL-5 EP doped oil with a viscosity of SAE 85W-140 is specified.

## According to the specifications of

API GL-5  
Ford SQ-M2C9002-AA  
ZF TE-ML 05A / 07A / 12E / 16B / 16C / 17B / 19B

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
14001	1 L	6	450
14020	20 L	1	30
14060	60 L	1	6
14205	205 L	1	2
14999	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.908	kg/l
Viscosity	85W-140	
Kinematic Viscosity at 40°C	367	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	26.1	mm <sup>2</sup> /s
Viscosity Index	95	
Flashpoint COC	215	°C
Pourpoint	-15	°C
Copper Corrosion	1B	

These characteristics are typical of current production. Variations in these characteristics may occur.