



# 16000CVT CVT Constant Variable Transmission Special Fluid

Document version: Apr 29, 2024



## Description

This premium synthetic high grade CVT fluid is used in various CVT transmissions that make use of a push-belt or steel chain. This transmission oil has been specially developed for Mercedes-Benz A and B class and Multitronic transmissions of the VAG group.

## According to the specifications of

BMW 83 22 0 136 376 / 83 22 0 429 154  
Chrysler CVT+4  
Daihatsu AMIX CVTF-DC  
Dodge CVT+4  
Ford M2C928-A  
GM DEX-CVT  
Honda HCF-2  
Jeep CVT+4  
MB 236.20  
Mitsubishi CVTF-J1 / CVTF-J4  
Nissan CVT Fluid NS-1 / CVT Fluid NS-2 / CVT Fluid NS-3  
Subaru ECVT / Lineartronic CVTF / i-CVT  
Suzuki CVT Green 1 / CVT Green 2  
Toyota CVT FE / TC  
VW G 052 180 / 052 516  
VW TL 52 180 / 52 516

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001CVT	1 L	6	450
16004CVT	4 L	4	112
16020CVT	20 L	1	30
16060CVT	60 L	1	6
16205CVT	205 L	1	2
16999CVT	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.848	kg/l
Colour	barnstone	
Viscosity	10W	
Kinematic Viscosity at 40°C	34	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	7	mm <sup>2</sup> /s
Viscosity Index	173	
Flashpoint COC	210	°C
Pourpoint	-52	°C
Brookfield Viscosity at -40°C	11900	mPa.s

These characteristics are typical of current production. Variations in these characteristics may occur.