



16000ULV ATF Automatic Transmission Fluid ULV

Document version: Apr 29, 2024



Description

This premium synthetic automatic transmission oil with high-quality base oils in combination with a balanced additive package ensures very good oxidation stability, excellent friction, anti-wear properties and excellent shifting performance. Due to the ultra-low viscosity, this ATF has a supreme fuel economy. The ultra-low viscosity fluid is mandatory for certain Ford and General Motors automatic transmissions.

Application manual

According to the specifications of

Aisin Warner AW-2
Ford Mercon ULV / WSS-M2C949-A
Opel/GM Dexron ULV

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001ULV	1 L	6	450
16004ULV	4 L	4	112
16020ULV	20 L	1	30
16060ULV	60 L	1	6
16205ULV	205 L	1	2
16999ULV	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density	0.847	kg/l	ASTM D4052
Colour	Red		
Kinematic Viscosity at 40°C	17.4	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	4,4	mm ² /s	ASTM D445
Viscosity Index	175		ASTM D2270
Flashpoint	182	°C	ASTM D92
Pourpoint	-54	°C	ASTM D6892

These characteristics are typical of current production. Variations in these characteristics may occur.