



# 16000ZF6 ATF Automatic Transmission Fluid M-1375.4

Document version: Apr 29, 2024



## Description

This premium synthetic automatic transmission oil has been specially developed for all 6 speed ZF transmissions and other applications for which manufacturers require an M-1375.4 specification.

## According to the specifications of

Aston Martin ATF M-1375.4  
BMW 83 22 0 142 516 / 83 22 2 305 396  
Bentley PY112995PA  
Hyundai 0400000C90SG  
Jaguar ATF M-1375.4 / Fluid 8432  
Land Rover TYK 500050  
Maserati 231603 / Gran Turismo ATF M-1375.4 / Quattroporte ATF M-1375.4  
Porsche ATF M-1375.4  
Rolls Royce ATF M-1375.4  
VW G 055 005

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001ZF6	1 L	6	450
16004ZF6	4 L	4	112
16020ZF6	20 L	1	30
16060ZF6	60 L	1	6
16205ZF6	205 L	1	2
16999ZF6	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.845	kg/l	
Colour	brown		
Viscosity	10W		
Kinematic Viscosity at 40°C	26.8	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	5.6	mm <sup>2</sup> /s	
Viscosity Index	151		
Flashpoint COC	210	°C	
Pourpoint	-51	°C	
Brookfield Viscosity at -40°C	8500	mPa.s	

These characteristics are typical of current production. Variations in these characteristics may occur.