



# 18000HR Gearbox Oil 75W-80 GL-4 Premium Synthetic Honda / Rover

Document version: Apr 29, 2024



## Description

This premium synthetic SAE 75W-80 HR transmission oil has been specially developed for use in Rover, MG, Honda and Land Rover manual transmissions and for those applications for which manufacturers require a SAE 75W-80 GL-4 specification.

## According to the specifications of

API GL-4  
Fiat 9.55550-MZ10 / 9.55550-MZ9  
Honda MTF-7289  
Renault B0032 / Annex 3  
Rover Group MTF 94  
Volvo 97305  
ZF TE-ML 01L / 02L / 08 / 16K

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
18001HR	1 L	6	450
18020HR	20 L	1	30
18060HR	60 L	1	6
18205HR	205 L	1	2
18999HR	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.860	kg/l
Viscosity	75W-80	
Kinematic Viscosity at 40°C	60	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	9	mm <sup>2</sup> /s
Viscosity Index	125	
Flashpoint COC	235	°C
Pourpoint	-39	°C

These characteristics are typical of current production. Variations in these characteristics may occur.