



## 39000G Industrial Gear Oil 460

Document version: Apr 29, 2024



### Description

This mineral industrial gearbox oil 460 has been specially developed for use in sealed gearboxes, equipped with straight, spiral, conical and worm gears.

### According to the specifications of

AGMA 9005-E02  
AISE 224  
DAVID BROWN S1.53.101E  
DIN 51517 part 3 CLP

### Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
|----------|--------|----------------|------------------|

### Standard analyses

| TEST                         | VALUE      | METHOD             |
|------------------------------|------------|--------------------|
| Density at 15°C              | 0.905      | kg/l               |
| Viscosity                    | ISO VG 460 |                    |
| Kinematic Viscosity at 40°C  | 434        | mm <sup>2</sup> /s |
| Kinematic Viscosity at 100°C | 27.6       | mm <sup>2</sup> /s |
| Viscosity Index              | 88         |                    |
| Flashpoint COC               | 260        | °C                 |
| Pourpoint                    | -18        | °C                 |
| Total Acid Number            | 0.38       | mgKOH/g            |
| FZG A/16,6/140               | 12         | level              |

These characteristics are typical of current production. Variations in these characteristics may occur.