



# 43000R 2-Stroke Oil Premium Synthetic Ester Racing Extreme

Document version: Apr 29, 2024



## Description

MPM 2-Stroke Oil Premium Synthetic Racing Extreme is specially developed for use in air- or water-cooled 2-stroke Racing-competition engines. This oil is only suitable where pre-mixed lubrication into the fuel is required for 2-stroke engines in Road-Racing and High-performance applications. The 100% Synthetic oil with Ester Technology provides extreme protection against wear in the engine, crank and pistons, under all racing conditions.

Note: **Not for use in oil-injection systems.**

Dosage: 3 to 4%

Recommended mixing ratio is for Racing 25:1

## According to the specifications of

API TC / TC+  
ISO L-EGB  
JASO FB

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
43001R	1 L	6	450
43020R	20 L	1	30
43060R	60 L	1	6
43205R	205 L	1	2
43999R	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.911	kg/l	ASTM D4052
Colour	Red		VISUAL
Kinematic Viscosity at 40°C	111	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	15.1	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	142		ASTM D2270
Flashpoint COC	240	°C	ASTM D92
Pourpoint	-30	°C	ASTM D6892
Total Base Number	2.9	mgKOH/g	ASTM D

These characteristics are typical of current production. Variations in these characteristics may occur.