



46000 Chainsaw Oil ISO-VG 100

Document version: Apr 29, 2024



Description

This chainsaw oil has been specially developed to lubricate the saw chain of chainsaws so that it does not stick or break. Important: Chainsaw oil is not suitable for the lubrication of the drive motor.

According to the specifications of

ISO VG-100

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 46001 | 1 L | 6 | 450 |
| 46005 | 5 L | 4 | 112 |
| 46020 | 20 L | 1 | 30 |
| 46060 | 60 L | 1 | 6 |
| 46205 | 205 L | 1 | 2 |
| 46999 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|------------|--------------------|
| Density at 15°C | 0.89 | kg/l |
| Viscosity | ISO VG 100 | |
| Kinematic Viscosity at 40°C | 100 | mm ² /s |
| Kinematic Viscosity at 100°C | 11.3 | mm ² /s |
| Viscosity Index | 98 | |
| Flashpoint COC | 230 | °C |
| Pourpoint | -25 | °C |

These characteristics are typical of current production. Variations in these characteristics may occur.