



51000A Fork Oil Light 5W Premium Synthetic

Document version: Apr 29, 2024



Description

MPM Motorcycle Fork Oil Light 5W Premium Synthetic is specially developed for use in telescopic front forks used in mopeds and road/off road motorcycles. The high deaeration properties of this fork oil means that there is minimum reduced foaming in the fork legs bodies. This gives optimal performance and stability so it will maintain optimal performance under extreme road/off-road conditions. MPM 5W Fork Oil provides excellent protection against wear and corrosion of suspension elements and seals, resulting in a higher performance level.

Note: Also suitable for telescopic forks of mountain bikes and bicycles where a SAE 5W oil is required.

According to the specifications of

SAE 5W

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
51001A	1 L	6	450
51020A	20 L	1	30
51060A	60 L	1	6
51205A	205 L	1	2
51999A	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.859	kg/l	
Colour	blue		
Viscosity	5W		
Kinematic Viscosity at 40°C	15.4	mm ² /s	
Kinematic Viscosity at 100°C	3.9	mm ² /s	
Viscosity Index	153		
Pourpoint	-57	°C	

These characteristics are typical of current production. Variations in these characteristics may occur.