



# 83000 Coolant -36°C Ready to Use

Document version: Apr 29, 2024

## Description

This standard coolant -36°C can be used throughout the whole year in the cooling systems of petrol and diesel engines. This coolant should be used undiluted and protects against freezing down to -36°C.

## Application manual

### According to the specifications of

AFNOR NF R 15-601  
ASTM D3306  
BS 6580  
SAE J 1034

## Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 83001    | 1 L    | 6              | 450              |
| 83005    | 5 L    | 4              | 112              |
| 83020    | 20 L   | 1              | 30               |
| 83060    | 60 L   | 1              | 6                |
| 83205    | 205 L  | 1              | 2                |
| 83999    | 1000 L | 1              | -                |

## Standard analyses

| TEST                                     | VALUE | METHOD |
|------------------------------------------|-------|--------|
| pH                                       | 8.1   |        |
| Density                                  | 1.13  | kg/l   |
| Colour                                   | Blue  |        |
| Freezing point at 1 antifreeze + 1 water | -36   | °C     |
| Boiling point                            | 108   | °C     |

These characteristics are typical of current production. Variations in these characteristics may occur.