



83000A Antifreeze G11 Concentrate

Document version: Apr 29, 2024



Description

This silicate-containing antifreeze VW TL 774C /G11 is a top quality antifreeze and can be used throughout the whole year in the cooling systems of petrol and diesel engines. Thanks to the special additives package and the high quality mono-ethylene glycol this MPM Antifreeze VW TL 774C /G11 is one of the highest quality on the market. This antifreeze should be further diluted before use with water in the recommended ratio.

According to the specifications of

ASTM D3306 (USA)
BEHR (Radiators)
BMW GS 94000 / N600 69 0
CUNA NC956-16
Deutz/MWM
GM/Opel
MB 325.0
ONORM V5123
UNE 26-361
VW TL 774C G11

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
83001A	1 L	6	450
83005A	5 L	4	112
83020A	20 L	1	30
83060A	60 L	1	12
83205A	205 L	1	2
83999A	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 20°C	1.125	kg/l
Colour	blue / green	
Ph 50% diluted	7.2	
Copper Corrosion	16	

These characteristics are typical of current production. Variations in these characteristics may occur.