



# 86000ALP Antifreeze Low Phosphate Concentrate

Document version: Apr 29, 2024



## Description

This Long life silicate-free antifreeze is based on Phosphated Organic Additive Technology (P-OAT) and is especially suitable for use in Japanese and Korean vehicles. This high quality antifreeze is extremely suitable in engines manufactured from aluminium, cast iron or combinations of the two metals and in cooling systems made of aluminium or copper alloys.

MPM 86000ALP antifreeze should be diluted with at least 30% demineralized water before use and does not contain nitrites, borates nor amines.

## According to the specifications of

ASTM D3306 / D6210  
Honda Type 2  
JIS K 2234-2006 Class II  
Mazda FL22  
Mitsubishi Dia Queen Super Long life Coolant  
Nissan L255N  
Subaru 16218  
Suzuki (Super) Long Life Coolant  
Toyota TSK 2601G-8A

## Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 86001ALP | 1 L    | 6              | 450              |
| 86005ALP | 5 L    | 4              | 112              |
| 86020ALP | 20 L   | 1              | 30               |
| 86060ALP | 60 L   | 1              | 6                |
| 86205ALP | 205 L  | 1              | 2                |
| 86999ALP | 1000 L | 1              | -                |

## Standard analyses

| TEST                       | VALUE     |      | METHOD        |
|----------------------------|-----------|------|---------------|
| Density at 15°C            | 1.119     | kg/l | ASTM<br>D1122 |
| Colour                     | dark blue |      |               |
| Freezing Point 50% diluted | -37       | °C   | ASTM<br>D1177 |
| pH                         | 8,4       |      | ASTM<br>D1287 |
| Boiling Point              | 178       | °C   | ASTM<br>D1120 |

These characteristics are typical of current production. Variations in these characteristics may occur.