



88000A Antifreeze MPG

Document version: Apr 29, 2024



Description

This MPM silicate-free MPG (Monopropylene glycol) antifreeze provides excellent protection of aluminium and metal alloy components within cooling systems. The non-toxic, environmentally friendly multipurpose product can also be used in boats and recreation vehicles (RVs) to protect inboard engines, drinking water and toilet systems against freezing. This Antifreeze MPG is environmentally friendly, and can be safely disposed of and is also suitable for food industry applications where applicable. This antifreeze should be diluted before use, as per manufacturer's specification.

According to the specifications of

VW TL 52 176

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 88005A | 5 L | 4 | 112 |
| 88020A | 20 L | 1 | 30 |
| 88060A | 60 L | 1 | 6 |
| 88205A | 205 L | 1 | 2 |
| 88999A | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|--|--------------------------|--------|
| Density at 20°C | 1.042 | kg/l |
| Colour | fluorescent orange / red | |
| Freezing point at $\frac{1}{3}$ antifreeze + $\frac{2}{3}$ water | -16 | °C |
| Freezing point at 1 antifreeze + 1 water | -36 | °C |
| Boiling Point | 165 | °C |
| Water | 4 | mass% |
| Copper Corrosion Test-reserve Alkanity | 6.3 | |

These characteristics are typical of current production. Variations in these characteristics may occur.