



65000A Lithium Calcium grease EP-2

Document version: May 6, 2024



Description

This lithium calcium EP-2 Grease has been specially developed for chassis points and ball clutches and universal joints. This grease reduces the number of re-lubrication operations for commercial vehicles, earth-moving machinery and agricultural machinery. Due to the water-repellent properties this grease is excellent for use in damp and dirty conditions.

According to the specifications of

DIN 51502
ISO 6743 / L-XBC IB2
KP2K-20

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 65000A | 0.4 kg | 12 | - |
| 65500A | 0.5 kg | 6 | - |
| 65001A | 1 kg | 6 | - |
| 65018A | 18 kg | 1 | - |
| 65050A | 50 kg | 1 | - |
| 65185A | 185 kg | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|-----------------------------|-----------------|--------------------|
| Colour | Red | |
| NLGI Classification | 2 | |
| Base Oil | Mineral | |
| Kinematic Viscosity at 40°C | 100 | mm ² /s |
| Temperature Range | -20 / 120 | °C |
| Soap Thickener | Lithium-Calcium | |

These characteristics are typical of current production. Variations in these characteristics may occur.