



02000 Motor Oil 15W-40 Turbo Universal

Document version: Apr 15, 2024



Description

This universal mineral motor oil has been specially developed for normal duty petrol engines and diesel engines of cars. This motor oil is also suitable for turbo diesel engines.

Application manual

According to the specifications of

ACEA A3/B4 / E2
API CG-4 / SL
Allison C4
Caterpillar TO-2
MAN M 271
MB 228.1
Volvo VDS

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 02001 | 1 L | 6 | 450 |
| 02004 | 4 L | 4 | 112 |
| 02005 | 5 L | 4 | 112 |
| 02020 | 20 L | 1 | 30 |
| 02060 | 60 L | 1 | 6 |
| 02205 | 205 L | 1 | 2 |
| 02999 | 1000 L | 1 | - |
| P02000 | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|--------|--------------------|
| Density at 15°C | 0.873 | kg/l |
| Viscosity | 15W-40 | |
| Kinematic Viscosity at 40°C | 90.5 | mm ² /s |
| Kinematic Viscosity at 100°C | 13.5 | mm ² /s |
| Viscosity Index | 151 | |
| Flashpoint COC | 200 | °C |
| Pourpoint | -30 | °C |
| Total Base Number | 8.4 | mgKOH/g |
| Sulphated Ash | 1 | mass% |

These characteristics are typical of current production. Variations in these characteristics may occur.