



04000 Motor Oil 10W-40 Semi Synthetic

Document version: Apr 15, 2024



Description

This semi synthetic universal motor oil has been developed for normal duty petrol, LPG and diesel engines of cars and light commercial vehicles.

According to the specifications of

ACEA A3/B4
API CF / SN
Fiat 9.55535-D2 / 9.55535-G2
MB 229.1
VW 501.01 / 502.00 / 505.00

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04001	1 L	6	450
04004	4 L	4	112
04005	5 L	4	112
04020	20 L	1	-
04060	60 L	1	-
04205	205 L	1	2
04999	1000 L	1	-
P04000	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0,858	kg/l	ASTM D4052
Viscosity	10W-40		SAE
Kinematic Viscosity at 40°C	91	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	14.1	mm ² /s	ASTM D445
Viscosity Index	159		ASTM D2270
Flashpoint COC	225	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	10.2	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.