



05000A Motor Oil 10W-40 Premium Synthetic Diesel

Document version: Apr 15, 2024



Description

This premium synthetic diesel motor oil is a fully synthetic engine oil. It provides superior protection for most Euro 4, Euro 5 and the latest Scania Euro 6 high-performance diesel engines. Recommended in a wide range of heavy duty applications, suitable for on-road and off-road transport, construction and agricultural industries. This 'long-drain' oil is specially developed for Scania engines which require the LDF-3 specification.

Application manual

According to the specifications of

ACEA E4 / E7
API CI-4
Cummins CES 20072
DAF Extended drain
Daimler Truck DTFR 15B120 (MB 228.5)
Deutz DQC III-10
MAN M 3277
MTU Type 3
Mack EO-N
Renault RD-2 / RLD / RLD-2 / RXD
Scania LDF-2 / LDF-3
Volvo VDS-3

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001A	1 L	6	450
05005A	5 L	4	112
05020A	20 L	1	30
05060A	60 L	1	6
05205A	205 L	1	2
05999A	1000 L	1	-
P05000A	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.870	kg/l
Viscosity	10W-40	
SAE	10W-40	
Kinematic Viscosity at 40°C	86.3	mm ² /s
Kinematic Viscosity at 100°C	13.3	mm ² /s
Viscosity Index	155	
Flashpoint COC	220	°C
Pourpoint	-39	°C
Total Base Number	16.1	mgKOH/g

These characteristics are typical of current production. Variations in these characteristics may occur.