



## 20000 Brake Fluid DOT 4

Document version: Apr 27, 2025



### Description

This DOT 4 brake fluid has been specially developed for use in all hydraulically operated brake and clutch systems fitted with drum or disk brakes and for which constructors specify a DOT 4 type brake fluid.

### According to the specifications of

FMVSS 116 DOT 4  
ISO 4925 (CLASS 4)  
SAE J 1704

### Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 20250    | 0.25 L | 12             | -                |
| 20000    | 0.5 L  | 12             | -                |
| 20001    | 1 L    | 6              | -                |
| 20004    | 4 L    | 4              | 112              |
| 20005    | 5 L    | 4              | 112              |
| 20020    | 20 L   | 1              | 30               |
| 20060    | 60 L   | 1              | 6                |
| 20205    | 205 L  | 1              | 2                |
| 20999    | 1000 L | 1              | -                |

### Standard analyses

| TEST                         | VALUE  | METHOD             |
|------------------------------|--------|--------------------|
| Density at 20°C              | 1.05   | kg/l               |
| Colour                       | yellow |                    |
| pH                           | 8      |                    |
| Kinematic Viscosity at 100°C | 2.3    | mm <sup>2</sup> /s |
| Kinematic Viscosity at -40°C | 1200   | mm <sup>2</sup> /s |
| Wet Boiling Point            | 168    | °C                 |
| Boiling Point                | 263    | °C                 |

These characteristics are typical of current production. Variations in these characteristics may occur.