



52000B 4-Stroke Motorcycle Oil 15W-50 Semi Synthetic

Document version: Apr 15, 2024



Description

MPM 4-Stroke Motorcycle Oil 15W-50 Semi Synthetic is specially developed for optimum lubrication of 4-stroke motorcycle engines. This oil has a wide viscosity range due to the flowability by low temperatures and high viscosity at high temperatures. This SAE 15W-50 has an excellent performance and makes this oil perfectly suitable in older motorcycle engines. The special formulation ensures cleaning and is suitable for lubrication of engines and gearboxes with or without wet plate clutches.

According to the specifications of

API SL
JASO MA / MA2

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
52001B	1 L	6	450
52020B	20 L	1	30
52060B	60 L	1	6
52205B	205 L	1	2

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.852	kg/l	ASTM D4052
Colour	Brown		VISUAL
Viscosity	15W-50		SAE
Kinematic Viscosity at 40°C	116.5	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	17.8	mm ² /s	ASTM D445
Viscosity Index	170		ASTM D2270
Flashpoint COC	237	°C	ASTM D92
Pourpoint	-36	°C	ASTM D97
Total Base Number	6.1	mgKOH/g	ASTM D2986

These characteristics are typical of current production. Variations in these characteristics may occur.