



# BLO30000 Marine Engine Oil Single Grade SAE 30

Document version: 18 Jun 2019



## Description

This marine engine Oil SAE 30 is a mineral oil developed for different purposes. Depending on the recommendation of the manufacturer this engine oil is used in diesel engines, hydraulic systems and light duty gearboxes. It is also used in the high power reversing clutches of vessels.

## Complies to the specifications of

SAE 30

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BLO30001	1 L	6	-
BLO30005	5 L	4	-
BLO30020	20 L	1	-
BLO30060	60 L	1	-
BLO30205	205 L	1	-
BLO30999	1000 L	1	-

TEST	VALUE	
Viscosity	SAE 30	
SAE	30	
Density at 15°C	0.891	kg/l
Kinematic Viscosity at 40°C	103	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	11.3	mm <sup>2</sup> /s
Viscosity Index	95	
Flashpoint COC	240	°C
Pourpoint	-21	°C
Total Base Number	4.4	mgKOH/g
Sulphated Ash	0.76	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.