



# 05000DX1 Motor Oil 5W-30 Premium Synthetic DX1

Document version: May 6, 2024



## Description

This premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs. Developed for better low speed pre-ignition (LSPI) protection, particularly for Opel/GM small displacement turbo charged engines. This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions. Due the excellent thin-flowability this engine oil offers excellent cold start properties.

## According to the specifications of

API SN Plus / SN-RC / SP / SP-RC  
Chrysler MS-13340 / MS-6395  
Fiat 9.55535-CR1  
Ford WSS-M2C946-A / WSS-M2C961-A1  
GM dexos™1 Gen 3 License No. D335ABDI046  
ILSAC GF-5 / GF-6A

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DX1	1 L	6	450
05005DX1	5 L	4	112
05020DX1	20 L	1	30
05060DX1	60 L	1	12
05205DX1	205 L	1	2
05999DX1	1000 L	1	-
P05000DX1	1 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.848	kg/l	ASTM D4052
Viscosity	5W-30		
Kinematic Viscosity at 40°C	60.7	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity at 100°C	10.8	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	172		ASTM D2270
Flashpoint COC	225	°C	ASTM D92
Pourpoint	-36	°C	ASTM D7346
Total Base Number	8.5	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.