



05000F Motor Oil 0W-30 Premium Synthetic Longlife II

Document version: May 6, 2024



Description

This premium synthetic Long Life II motor oil has been specially developed for VAG engines equipped with first generation pump injectors. This motor oil meets the requirements set out by VW 503.00/506.00/506.01.

According to the specifications of

ACEA A5/B5
VW 503.00 / 506.00 / 506.01

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001F	1 L	6	450
05005F	5 L	4	112
05020F	20 L	1	30
05060F	60 L	1	6
05205F	205 L	1	2
05999F	1000 L	1	-
P05000F	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.865	kg/l
Viscosity	0W-30	
Kinematic Viscosity at 40°C	55.3	mm ² /s
Kinematic Viscosity at 100°C	10.1	mm ² /s
Viscosity Index	174	
Dynamic Viscosity at -30°C	3100	mPa.s
Flashpoint COC	226	°C
Pourpoint	-50	°C
Total Base Number	10.2	mgKOH/g
Sulphated Ash	1.28	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.