



50000SCF Shift Control Fluid

Document version: May 6, 2024



Description

This shift control premium synthetic hydraulic fluid has been specially developed for electrohydraulic transmissions, known as Selespeed systems at the Fiat group. The Selespeed system is used by numerous manufacturers such as Aston Martin, Citroën, Peugeot and GM/Opel.

According to the specifications of

Fiat 9.55550-SA1
Opel/GM 1940 774

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 50001SCF | 1 L | 6 | 450 |
| 50020SCF | 20 L | 1 | 30 |
| 50060SCF | 60 L | 1 | 6 |
| 50205SCF | 205 L | 1 | 2 |
| 50999SCF | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|-------|--------------------|
| Density | 0.83 | kg/l |
| Kinematic Viscosity at 100°C | 6.8 | mm ² /s |
| Kinematic Viscosity at -40°C | 1900 | mm ² /s |
| Viscosity Index | 270 | |
| Flashpoint COC | 164 | °C |
| Pourpoint | -51 | °C |

These characteristics are typical of current production. Variations in these characteristics may occur.