



87000AEVO Antifreeze Premium Longlife G12evo Concentrate

Document version: May 6, 2024



Description

This Premium Long-Life antifreeze is silicate-containing, based on OAT, which among other specifications meets the latest requirements of VAG models 2018 onwards and where G12evo is recommended. This concentrate is also suitable for VAG models where G12+, G12++ or G13 is recommended.

This Premium Long-Life antifreeze should be diluted with the recommended quantity of demineralized water before use.

This antifreeze is also free from nitrites, amines, borates and 2-ethylhexanoic acid.

Application manual

Freezing Point 33 vol % diluted -18°C (first crystal) Freezing Point 50 vol % diluted -38°C (first crystal) Freezing Point 60 vol % diluted -50°C (first crystal)

According to the specifications of

MAN 324 Si-OAT evo
MB 325.5 / 325.6
VW TL 774L G12evo

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
87001AEVO	1 L	6	450
87005AEVO	5 L	4	112
87020AEVO	20 L	1	30
87060AEVO	60 L	1	6
87205AEVO	205 L	1	2
87999AEVO	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 20°C	1.121	kg/l	ASTM D4052
Colour	Pink		
Freezing Point 50% diluted	40	°C	ASTM D1177
Ph 50% diluted	7.5 - 8.5		ASTM D1287
Ph	8.4 - 8.9		ASTM D1287
Boiling Point	>170	°C	ASTM D1120
Water	5	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.