



16000CVT CVT Constant Variable Transmission Special Fluid

Document version: May 6, 2024



Description

This premium synthetic high grade CVT fluid is used in various CVT transmissions that make use of a push-belt or steel chain. This transmission oil has been specially developed for Mercedes-Benz A and B class and Multitronic transmissions of the VAG group.

According to the specifications of

BMW 83 22 0 136 376 / 83 22 0 429 154
Chrysler CVT+4
Daihatsu AMIX CVTF-DC
Dodge CVT+4
Ford M2C928-A
GM DEX-CVT
Honda HCF-2
Jeep CVT+4
MB 236.20
Mitsubishi CVTF-J1 / CVTF-J4
Nissan CVT Fluid NS-1 / CVT Fluid NS-2 / CVT Fluid NS-3
Subaru ECVT / Lineartronic CVTF / i-CVT
Suzuki CVT Green 1 / CVT Green 2
Toyota CVT FE / TC
VW G 052 180 / 052 516
VW TL 52 180 / 52 516

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001CVT	1 L	6	450
16004CVT	4 L	4	112
16020CVT	20 L	1	30
16060CVT	60 L	1	6
16205CVT	205 L	1	2
16999CVT	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.848	kg/l
Colour	barnstone	
Viscosity	10W	
Kinematic Viscosity at 40°C	34	mm ² /s
Kinematic Viscosity at 100°C	7	mm ² /s
Viscosity Index	173	
Flashpoint COC	210	°C
Pourpoint	-52	°C
Brookfield Viscosity at -40°C	11900	mPa.s

These characteristics are typical of current production. Variations in these characteristics may occur.