



55000 4-Stroke Motorcycle Oil 15W-50 Premium Synthetic Ester

Document version: May 6, 2024



Description

MPM 4-Stroke Motorcycle Oil 15W-50 Premium Synthetic Ester is suitable for air- and water-cooled 4-stroke motorcycle engines. New technology requires advanced motor oil, this oil with a balanced additive package with ester additives provide the perfect protection, it will reduce oil consumption and extend the life of the engine even under the highest circumstances. This multi-grade SAE 15W-50 engine oil has been developed for road and off-road motorcycle engines.

Note: This engine oil is suitable for gearbox lubrication with or without wet clutches and is backwards compatible with API: SG, SH, SJ, SL, and SM specifications.

According to the specifications of

API SN
JASO MA / MA2

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
55001	1 L	6	450
55020	20 L	1	30
55060	60 L	1	6
55205	205 L	1	2
55999	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.854	kg/l	ASTM D4052
Colour	Red		VISUAL
Viscosity	15W-50		
Kinematic Viscosity at 40°C	117	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	18.6	mm ² /s	ASTM D445
Viscosity Index	179		ASTM D2270
Pourpoint	-45	°C	ASTM D7346
Total Base Number	7.3	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.